

Technical data sheet UPL VV 1124 K1

Product information		
Chemical name	Chrome antimony titanium buff rutile	
Chemical formula	(Ti,Cr,Sb)O <sub>2</sub>	
Colour index	Pigment brown 24	
C.I. No.	77310	
CAS No.	68186-90-3	
EINECS No.	269-052-1	

Physical data	
Appearance	Brown powder
Apparent Density (g/cc)	0.75 to 0.85
Specify gravity (g/cm³)	4.5 Approx.
Moisture content (%)	1.0 Max
Water soluble matter	1.0 Max
Oil absorption (% by wt.)	16 ± 5
Median particle diameter (μ)	2.8 Max
Residue on 45µm sieve (% by wt.)	0.1 Max
рН	6.0 to 8.0

Regulatory information		
Germany BfR recom. IX	Complies	
AP 89/1	Complies	
USA (FDA) 21 CFR § 178.3297	Listed	
Toys Europe EN 71-3	Complies	
Toys USA ASTM F 963-03	Complies	
CONEG, EC 94/62	Complies	
RoHS, 2002/95/EC, 2005/618/EC	Complies	
End of Life Vehicles, 2000/53/EC,2002/525/EC	Complies	

## Standard packaging

25 Kg paper bags with LDPE liner inside

Paper / Palletization can be altered & offered based on request

Mass tone	Tint tone

Fastness properties	
Heat resistance	800° C
Solvent resistance	5
Acid resistance	5
Alkali resistance	5
Light fastness	8
Weather fastness	5

- a) Solvent is added to the pigment and assessment on grey scale is done as per DIN EN ISO 20105-A02 (1-Severe; 5-No degradation)
- By adding 10% hydro chloric acid and 10% sodium hydroxide to the pigment
- Light fastness was tested in an alkyd system and assessment done using wool scale as per DIN EN ISO 105-B01 (8 - Extremely good)
- d) Weather fastness was tested in waterborne acrylic resin system and assessment done using grey scale as per DIN EN ISO 20105-A02 after 2000 hours accelerated weathering

# **Chemical inventory status**

Listed in the following national chemical inventories: AICS (Australia), DSL (Canada), ECL (Korea), EINECS (Europe), IECSC (China), MITI (Japan), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA).

## **Toxicity**

Least toxic and a safe pigment for industrial applications. It is ecologically non-hazardous and does not create any skin or eye irritation

#### **Application areas**

RPVC, Poly olefins, Engineering resins, Ceramics, Paints and Coatings etc.,

## Disclaimer:

Our product specifications, application related information and additional information in this document are based on our current state of knowledge. The shade indicated here is only for reference and may vary based on the dilution medium and background.

This information is provided for reference only. This can be changed without prior notice.

Ultramarine & Pigments Ltd., 25-B, SIPCOT Industrial complex, Ranipet-632403, Tamil Nadu, India

Email: pigments@ultramarinepigments.net, exports@ultramarinepigments.net

Rev. No: 0 Issue on: 30/08/2019