

TECHNICAL DATA SHEET ULTRAMARINE BLUE UPL 8011

GENERAL INFORMATION:

1. IDENTITY : Sodium Aluminium Sulpho Silicate

2. CAS NUMBER : 57455-37-5 / 101357-30-6

3. COLOUR INDEX NUMBER : Pigment Blue 29 | C.I.No. 77007

COLOUR PROPERTIES:

(Blue reduced with five times its weight of Rutile Titanium Dioxide, drawn down and compared with its Batch Standard in CIE Lab Scale)

1. TINTING STRENGTH (%) : 100 ± 5

2. COLOUR DIFFERENCE DE* : 1.0 Unit Maximum

 DL^* : ± 0.5 Unit DA* : ± 0.5 Unit DB* : ± 0.5 Unit

OTHER PHYSICAL AND CHEMICAL PROPERTIES:

1. APPEARANCE : Blue Powder
2. APPARENT DENSITY (g/cc) : 0.45 to 0.60
3. MOISTURE CONTENT AT 105°C (% BY WT.) : 1.0 % Maximum
4. WATER SOLUBLE MATTER (% BY WT.) : 2.0% Maximum
5. FREE SULPHUR : 100 ppm Maximum

6. OIL ABSORPTION (% BY WT.) : 34 to 37

7. MEDIAN PARTICLE DIAMETER : 2.0 Microns Maximum

8. RESIDUE ON 45 MICRONS SIEVE (% BY WT.): 0.2 Maximum

COLOUR FASTNESS PROPERTIES:

1. HEAT STABILITY : 350 °C for 5 Minutes

2. LIGHT (DAY LIGHT AND XENON LAMP)

IN MASS TONE : 7/8 on Wool scale IN REDUCED TONE : 7/8 on Wool scale : 7/8 on Grey scale : 4/5 on Grey scale

4. IN ACIDS : Poor 5. IN ALKALIS : Good

TOXICITY:

Least toxic and a safe pigment for industrial applications. It is ecologically non-hazardous and does not create any skin irritation.

USAGE IN COSMETICS:

Conforms to various regulations in most of the countries in the world.

Note:

The information provided above is for general guidelines only and subject to change without notice. Ultramarine & Pigments Limited assumes no responsibility and users are advised to test the products for suitability prior to use on a commercial or production scale.